

MAXIMIZE YOUR IMPACT®

FULL COLOR MESSAGE CENTERS



Many sizes are available. Your local Nevco Display and Scoring Consultant will review all aspects of the project with you, ensuring the correct display type and matrix size is selected.

- Moving messages capture your audience's attention and maximize revenue generation opportunities
- Wired/Wireless control options
- Fast display rate (30 frames per second) ensures graphics and video appear realistic and smooth
- All message centers feature a full matrix design; display graphics and text full screen
- Increased flexibility vs. static signs
- Exceptional viewing angles; display is easily viewed from all directions
- Adapts easily for any installation method
- Unique design for low power consumption



**BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:
WWW.NEVCO.COM**

**U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360
FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM**

INTEGRATED DISPLAY AND SCORING SOLUTIONS

20mm True Color

CABINET SIZE	VIEWING MATRIX	NUMBER OF LINES		CHARACTER HEIGHT RANGE		CHARACTERS PER LINE		ACTUAL WEIGHT		MAXIMUM POWER	
		Hx W	HxW	Min. Char. Size	Max Char. Size	Min. Char. Size	Max Char. Size	Min. Char. Size	Max Char. Size	Lbs.	Watts
2' x 10'	24 x 144	3	1	5.5"	18"	28	7	152	816	6.8	3.4
3' x 8'	40 x 112	5	1	5.5"	31"	22	4	190	1056	8.8	4.4
3' x 10'	40 x 144	5	1	5.5"	31"	28	5	245	1356	11.3	5.7
3' x 12'	40 x 176	5	1	5.5"	31"	35	6	305	1656	13.8	6.9
4' x 8'	56 x 112	7	1	5.5"	44"	22	3	238	1476	12.3	6.2
4' x 10'	56 x 144	7	1	5.5"	44"	28	4	417	1896	15.8	7.9
4' x 12'	56 x 176	7	1	5.5"	44"	35	4	406	2316	19.3	9.7
4' x 16'	56 x 240	7	1	5.5"	44"	48	6	536	3156	26.3	13.2
6'9" x 9'5"	96 x 144	12	1	5.5"	72"	28	2	507	3240	27	13.5
6'9" x 12'7"	96 x 192	12	1	5.5"	72"	38	2	676	4320	36	18
6'9" x 15'9"	96 x 240	12	1	5.5"	72"	48	3	845	5400	45	22.5

20mm True Color	
PIXEL PITCH	20mm (0.78"); 232 pixels per sq. ft.
COLOR	Full 24-bit true color
COLOR CAPABILITY	16.7 million colors
DISPLAY ELEMENT	3 LEDs per pixel
PIXEL BRIGHTNESS	7,000 NIT (cd/m2)
VIEWING ANGLE	Horizontal: 140 degrees / Vertical: 60 degrees
OPERATING TEMP	-40°- 150° F
CONTRAST ENHANCEMENT	Horizontal louvers
CONTROLLER	Standard Windows based PC or Laptop (not included)
MESSAGE STORAGE	Solid State Flash (no moving parts for high reliability); compressed image format
GRAPHIC CAPABILITIES	Text, animations, logos, multiple fonts, moving messages, corporate advertising, time & temperature, etc
CONTROL SOFTWARE	Nevco Composer™ creation and scheduling software, included with purchase price of each message center
COMMUNICATION OPTIONS	Ethernet (Cat5 or fiber cable) or RF Wireless
POWER	Input: 85 - 265 VAC; Power factor correction for reduced power consumption
DISPLAY DIMMING	16 levels of brightness/auto dimming
DISPLAY CABINET	Reinforced cabinet; weather resistant aluminum
PAINT	Weather resistant with UV inhibitor for long-lasting, durable black finish (PMS by quote)
COMPLIANCE INFORMATION	CUL, UL Listed; FCC, CE Industry Canada
OPERATING ENVIRONMENT	Outdoor/Indoor
GUARANTEE	5 Year limited guarantee

Additional sizes are available. Your local Nevco Display and Scoring Consultant will review all aspects of the project with you, ensuring selection of the correct display type and matrix.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: WWW.NEVCO.COM/INFO/GUARANTEE.PHP
U.S. SERVICE: 1-800-851-4040. INTERNATIONAL SERVICE: 1-618-664-0360. CANADA SERVICE: 1-800-461-8550.



BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:
WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360
 FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM