

# BASEBALL & SOFTBALL

#### ACCESSORIES

# MODEL MPCX

**Size:** 3.25" x 5.5" x .875" (.08 x .14 x .02 m) **Approximate weight each:** 5.5 oz. (.16 kg) **Display:** 32 character LCD **Keypad:** 12 keys



### Small and light-weight control featuring:

- Convenient wireless operation within 1000'.
- Operate multiple scoreboards simultaneously.
- System allows multiple controllers to link to individual scoreboards.
- · High visibility LCD display with a sealed keyboard.
- Long battery life with indicator; two AA batteries included.
- Single hand operation with a no slip grip.
- Small enough to fit in a shirt pocket and can be attached to a waist band using the built-in clip.
- Built-in wireless signal strength meter and internal antenna.



BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

## **INTEGRATED DISPLAY AND SCORING SOLUTIONS**

## Model MPCX Baseball/Softball Operating Features



LCD DISPLAY (16 characters x 2 lines)

POWER ON / OFF SWITCH

BALL (ADDS 1)

(hold to clear Balls and Strikes)

STRIKE (ADDS 1)

(hold to clear Balls and Strikes)

**OPTIONS KEY**, allows you to:

- Log Overscore (for scoreboards that show scores by inning)
- Clear Scoreboard
- · Set Brightness of Scoreboard
- Check Battery Level
- · Check Signal Strength
- Set Security Level
- Re-link Control
- Select Scoreboard Type

OUT (ADDS 1)

(hold to clear Balls, Strikes and Outs)

#### ADDITIONAL SPORT-SPECIFIC CONTROLS AVAILABLE:

















CERTIFICATIONS: FCC part 15 Class B, CE, ROHS.

**CONTROL:** One (1) each MPCX Microprocessor-based operator's control. Constructed of black, highly break-resistant ABS plastic. Size 3 1/4" x 5 1/2" x 7/8" (.08 x .14 x .02 meters), built-in antenna, weight is 5 1/2 oz. (.16 kg). Control features include: On/Off key. 12-key keyboard with sport specific keyboard overlay. Control may be re-programmed by the user to operate other wireless Nevco scoreboards of the same sport

RANGE: Maximum range of 1000 feet from control to receiver.

**POWER:** Control: Battery operated, requires 2 each "AA" batteries. (Batteries supplied with control.) Receiver, INPUT: 120/240 VAC, .15/.07 Amps, 50/60 Hz.

**OPERATES MODELS:** 1500, 1503, 1506, 1508, 1510, 1515 Timer, 1520 Timer, 1525 Timer, 1530, 1535, 1550. 9505 compatible with scoreboards with timers.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: WWW.NEVCO.COM/INFO/GUARANTEE.PHP U.S. SERVICE: 1-800-851-4040. INTERNATIONAL SERVICE: 1-618-664-0360. CANADA SERVICE: 1-800-461-8550.



BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360 FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM