

Advanced timing features ideal for Soccer, Football, Baseball, Softball, Field Hockey and Lacrosse facilities.

- Operate wired or wireless.
- Bright, long lasting, energy efficient LEDs.
- Gasketed digits reduces water intake.
- Includes Possesion Indicator and built-in Horn.
- Lighted time colon and decimal; automatically adjusts to 1/10th of a second.
- * Translucent White LEDs cannot be intermixed with other digit colors on one scoreboard.



BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT: WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360 FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

INTEGRATED DISPLAY AND SCORING SOLUTIONS



Model 3604 (Outdoor) Soccer/Lacrosse/Field Hockey Scoreboard

SCOREBOARD/CONTROL OPERATING FEATURES

MODEL 3604	MPC(W)-4/5/6	MPCW-7	MPCX ₂ WIRELESS			
TIMING 30" High Intensity Red, Amber, or Translucent White LED Digits	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.			
TEAM SCORES 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	Displays 0-99			
QUARTER 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-9	Displays 0-9	Displays 0-9			
HOME SHOTS 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	Displays 0-99			
GUEST SHOTS 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	Displays 0-99			
PENALTY KICK INDICATORS High Intensity Red, Amber, or Translucent White LED	One for each team shaped in the form of a football.	One for each team shaped in the form of a football.	N/A			
TIME OF DAY	In place of displaying game time on the score- board, the "time out" time may be displayed or the "time of day".	In place of displaying game time on the score- board, the "time out" time may be displayed or the "time of day".	N/A			
HORN	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	seconds. May omit automatic horn. of two (2) seconds. May omit automatic horn. of two (2) seconds. M				
JUNCTION BOX	One (1) 4" x 2 1/8" x 2 1/8" with cover, to be installed in dry location (press box), furnished.	N/A	N/A			
CONTROL CABLE	One (1) length required of 2-WIRE (coaxial type) ¼″ diameter. Order length required.	N/A	N/A			
SEGMENT TIMING	Supported. the standard 15 colors, Nevco can match any PMS c	Supported.	Requires $MPCX_2$ segment timer control.			

colors, Nevco can match any PNIS color. Please contact your local Display and Scoring Consultant for pricing information.

#103 Cardinal Red	#73 Maroon	#102 Team Orange	#99 Golden Yellow	Kelly	#74 Forest Green	#120 Teal Blue	#72 Electronic Blue	#140 Royal Blue	Midnight	#141 Navy Blue	#70 Desert Tan	#95 Silver Gray	#76 Print Black

AGENCY APPROVAL: UL/CUL listed, FCC, CE, INDUSTRY CANADA.

SCOREBOARD: Size 30'L x 10'H x 8"D (9.14 x 3.05 x .20 meters), constructed of aluminum. Scoreboard has 1" white outline striping. Eight (8) brackets provided for mounting. Hanging weight approximately 630 lbs. (286 kg) with ETNs: 692 lbs. (314 kg). 2.5 Amps, 50/60 Hz. Requires earth ground. CAPTIONS: TIME, black 15" high. HOME, GUESTS, QTR, SHOTS (2), white 15" high.

(HOME and GUESTS are omitted when ordered with ETNs.) **LED UNITS:** Seven-bar segmented digits with protective aluminum cover.

BUILT-IN LIGHTNING PROTECTION: All models feature fiber-optic

isolation circuitry providing additional protection against lightning strikes.

POWER WITHOUT ETNS (RED/AMBER): 120 VAC, 3.2 Amps, 50/60 Hz. / 240 VAC, 1.6 Amps, 50/60 Hz. Requires earth ground. POWER WITH ETNS (RED/AMBER): 120 VAC, 4.9 Amps, 50/60 Hz. / 240 VAC,

POWER WITHOUT ETNS (TRANSLUCENT WHITE): 120 VAC, 5.4 Amps, 50/60 Hz. / 240 VAC, 2.7 Amps, 50/60 Hz. Requires earth ground.

POWER WITH ETNS (TRANSLUCENT WHITE): 120 VAC, 7.0 Amps, 50/60 Hz. / 240 VAC, 3.5 Amps, 50/60 Hz. Requires earth ground.

es. GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: NEVCO.COM/WARRANTY-LIMITATION

U.S. SERVICE: 1-800-851-4040

INTERNATIONAL SERVICE: 1-618-664-0360

CANADA SERVICE: 1-800-461-8550



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT: WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360 FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM