

Advanced timing features ideal for combination Football, Baseball, Softball, Soccer, Lacrosse and Field Hockey facilities.

- Operate wired or wireless.
- Bright, long lasting, energy efficient LEDs.
- Gasketed digits reduces water intake.
- Includes Possession Indicators, Time Outs Left and built-in Horn.
- Lighted time colon and decimal; automatically adjusts to 1/10th of a second.
- * Translucent White LEDs cannot be intermixed with other digit colors on one scoreboard



BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT: WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360 FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

INTEGRATED DISPLAY AND SCORING SOLUTIONS

Model 3616 (Outdoor) Football Scoreboard SCOREBOARD/CONTROL OPERATING FEATURES											
MODEL 3616	MPC(W)-4/5/6	MPCW-7	MPCX ₂ WIRELESS								
TIMING 30" High Intensity Red, Amber, or Translucent White LED Digits	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute.								
TEAM SCORES 30" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	Displays 0-99								
TIME OUTS LEFT 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-9	Displays 0-9	Displays 0-9								
QUARTER 30" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-9	Displays 0-9	Displays 0-9								
BALL ON 30" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	Displays 0-99								
DOWN 30" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-9	Displays 0-9	Displays 0-9								
YDS TO GO 30" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	Displays 0-99								
BALL POSSESSION INDICATORS High Intensity Red, Amber, or Translucent White LED	One for each team shaped in the form of a football.	One for each team shaped in the form of a football.	One for each team shaped in the form of a football.								
TIME OF DAY	In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day".	In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day".	N/A								
HORN	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.								
JUNCTION BOX	One (1) 4" x 2 1/8" x 2 1/8" with cover, to be installed in dry location (press box), furnished.	N/A	N/A								
CONTROL CABLE	One (1) length required of 2-WIRE (coaxial type) 1⁄4" diameter. Order length required.	N/A	N/A								
SEGMENT TIMING	Supported.	Supported.	Requires $MPCX_2$ segment timer control.								

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.

#103 #73 Cardinal Maroo	#102 Dn Team	#99 Golden		#74 Forest	#120 Teal	#72 Electron-		#121 Midnight	#141 Navy	#104 Medium	#70 Desert	#95 Silver	#76 Print
----------------------------	-----------------	---------------	--	---------------	--------------	------------------	--	------------------	--------------	----------------	---------------	---------------	--------------

AGENCY APPROVAL: UL/CUL listed, FCC, CE, INDUSTRY CANADA.

SCOREBOARD: Size 36'L x 10'H x 8"D (10.97 x 3.05 x .20 meters),

constructed of aluminum. Scoreboard has 2" white outline striping.

Four lengths of angle iron and Four (4) brackets provided for mounting.

Hanging weight approximately 1020 lbs. (463 kg) with ETNs 1220 lbs. (553 kg).

CAPTIONS: HOME, GUESTS, DOWN, YDS TO GO, QTR, BALL ON, T.O.L. (2), white 15" high. (HOME

and GUESTS are omitted when ordered with ETNs.)

LED UNITS: Seven-bar segmented digits with protective aluminum cover.

BUILT-IN LIGHTNING PROTECTION: All models feature fiber-optic isolation circuitry providing ad-

ditional protection against lightning strikes.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: NEVCO.COM/WARRANTY-LIMITATION/

U.S. SERVICE: 1-800-851-4040 INTERNATIONAL SERVICE: 1-618-664-0360 CANADA SERVICE: 1-800-461-8550



MAXIMIZE YOUR IMPACT[®]

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT: WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360 FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

POWER WITHOUT ETNS (RED/AMBER): 120 VAC, 4.5 Amps, 50/60 Hz. / 240 VAC, 2.2 Amps, 50/60 Hz. Requires earth ground.

POWER WITH ETNS (RED/AMBER): 120 VAC, 8.0 Amps, 50/60 Hz. / 240 VAC, 4.0 Amps, 50/60 Hz. Requires earth ground.

POWER WITHOUT ETNS (TRANSLUCENT WHITE): 120 VAC, 7.7 Amps, 50/60 Hz. / 240 VAC, 3.8 Amps, 50/60 Hz. Requires earth ground.

POWER WITH ETNS (TRANSLUCENT WHITE): 120 VAC, 10.9 Amps, 50/60 Hz. / 240 VAC, 5.4 Amps, 50/60 Hz. Requires earth ground.