



BASEBALL & SOFTBALL

SCOREBOARDS

MODEL 1640

Size: 18' x 8' x 8" (5.48 x 2.44 x .20 meters)

Approximate hanging weight: 420 lbs. (191 kg) **With ETNs:** 482 lbs. (219 kg)

Digit Size: 18" **Digit Color:** High Intensity Red, Amber, or Translucent White

INNING	BALL	STRIKE	OUT
1	3	2	2
NEVCO			
	RUNS	HITS	ERRORS
GUESTS	12	13	3
HOME	13	11	1

INNING	BALL	STRIKE	OUT
1	3	2	2
NEVCO			
	RUNS	HITS	ERRORS
GUESTS	12	13	3
HOME	13	11	1

SHOWN WITH OPTIONAL WHITE LEDS

INNING	BALL	STRIKE	OUT
1	3	2	2
NEVCO			
	RUNS	HITS	ERRORS
EAGLES	12	13	3
PANTHERS	13	11	1

SHOWN WITH OPTIONAL ELECTRONIC TEAM NAMES

Scoreboard designed for combination Baseball/Softball facilities.

- Designed to withstand wind load speed zones exceeding 150 mph.
- Operate wired or wireless.
- Includes Hit and Error Totals.
- Bright, long lasting, energy efficient LEDs.
- Gasketed digits reduces water intake.
- Flush sign mounting.

* Translucent White LEDs cannot be intermixed with other digit colors on one scoreboard



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

INTEGRATED DISPLAY AND SCORING SOLUTIONS



Model 1640 (Outdoor) Baseball/Softball Scoreboard

SCOREBOARD/CONTROL OPERATING FEATURES

MODEL 1640	MPC(W)-4/5/6	MPCW WIRELESS	MPCX ₂ WIRELESS
INNING 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays 1-19	Displays 1-19	Displays 0-19
BALL 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays Blank-9	Displays Blank-9	Displays 0-9
STRIKE 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays Blank-9	Displays Blank-9	Displays 0-9
OUT 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays Blank-9	Displays Blank-9	Displays 0-9
RUNS 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	Displays Blank-99
HITS 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays Blank-99	Displays Blank-99	Displays Blank-99
ERRORS 18" High Intensity Red, Amber, or Translucent White LED Digits	Displays Blank-9	Displays Blank-9	Displays Blank-9
PITCH COUNT	N/A	Supported. Integrates with PCD display. Controlled by hand-held switches.	Supported. Integrates with PCD display. Requires Pitch Count MPCX ₂ control.
PITCH TIMER	N/A	Supported. Integrates with 9520 display. Controlled by hand-held switches.	Supported. Integrates with 9520 display. Requires SCD/DGT MPCX ₂ control.

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.

#103 Cardinal Red	#73 Maroon	#102 Team Orange	#99 Golden Yellow	#142 Kelly Green	#74 Forest Green	#120 Teal Blue	#72 Electronic Blue	#140 Royal Blue	#121 Midnight Blue	#141 Navy Blue	#104 Medium Purple	#70 Desert Tan	#95 Silver Gray	#76 Print Black
-------------------------	---------------	------------------------	-------------------------	------------------------	------------------------	----------------------	---------------------------	-----------------------	--------------------------	----------------------	--------------------------	----------------------	-----------------------	-----------------------

AGENCY APPROVAL: UL/CUL listed, FCC, CE, INDUSTRY CANADA.

SCOREBOARD: Size 18'L x 8'H x 8"D (5.48 x 2.44 x .20 meters), constructed of aluminum. Scoreboard has 1" white outline striping. Hanging weight approximately 420 lbs. (191 kg) or 482 lbs. (219 kg) with ETNs.

CAPTIONS: HOME & GUESTS, white letters 12" high. INNING, BALL, STRIKE, OUT, RUNS, HITS, ERRORS, white letters 10" high. (HOME and GUESTS are omitted when ordered with ETNs.)

LED UNITS: Seven-bar segmented digits with protective aluminum cover.

BUILT-IN LIGHTNING PROTECTION: All models feature fiber-optic isolation circuitry providing additional protection against lightning strikes.

POWER WITH ETNS (RED/AMBER): 120 VAC, 2.9 Amps, 50/60 Hz. / 240 VAC, 1.5 Amps, 50/60 Hz. Requires earth ground.

POWER WITHOUT ETNS (RED/AMBER): 120 VAC, 1.8 Amps, 50/60 Hz. / 240 VAC, .9 Amps, 50/60 Hz. Requires earth ground.

POWER WITH ETNS (TRANSLUCENT WHITE): 120 VAC, 4.1 Amps, 50/60 Hz. / 240 VAC, 2.0 Amps, 50/60 Hz. Requires earth ground.

POWER WITHOUT ETNS (TRANSLUCENT WHITE): 120 VAC, 3.0 Amps, 50/60 Hz. / 240 VAC, 1.5 Amps, 50/60 Hz. Requires earth ground.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: NEVCO.COM/WARRANTY-LIMITATION/

U.S. SERVICE: 1-800-851-4040

INTERNATIONAL SERVICE: 1-618-664-0360

CANADA SERVICE: 1-800-461-8550



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:
WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360
FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM