



OUTDOOR MULTI-SPORT

SCOREBOARDS

MODEL 7685



Size: 24' x 8' x 8" (7.31 x 2.44 x .20 meters)

Approximate hanging weight: 740 lbs. (336 kg)

Digit Size: 24"/18" **Digit Color:** High Intensity Red, Amber, or Translucent White



Shown with FinishLynx® Interface



Shown in Translucent White



Intelligent Captions™ CHANGE AUTOMATICALLY between Track, Football, Baseball, Soccer, Lacrosse and Field Hockey facilities.

- Operate wired or wireless.
 - Bright, long lasting, energy efficient LEDs.
 - Gasketed digits reduces water intake.
 - Lighted time colon and decimal; automatically adjusts to 1/10th of a second.
 - When operating as a track board, the 1/1000th of a second displays.
 - All 7600 Series models are compatible with third-party timing systems.
- * **Translucent White LEDs cannot be intermixed with other digit colors on one scoreboard.**



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:
WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360
FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

INTEGRATED DISPLAY AND SCORING SOLUTIONS



Model 7685 (Outdoor) Multi-Sport Scoreboard

SCOREBOARD/CONTROL OPERATING FEATURES

MODEL 7685	MPC(W)-4/5/6	MPCW-7	MPCX WIRELESS Not available with ETNs
TIMING 24" High Intensity Red, Amber, or Translucent White LED Digits	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute. 1/1000th seconds, track only.	Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute. 1/1000th seconds, track only.	N/A
RUNNER 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	N/A
LANE 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-9	Displays 0-9	N/A
EVENT 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	N/A
PLACE 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	N/A
ROUND 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	N/A
HEAT 24" High Intensity Red, Amber, or Translucent White LED Digits	Displays 0-99	Displays 0-99	N/A
TIME OF DAY	In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day".	In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day".	N/A
HORN	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time.	N/A
JUNCTION BOX	One (1) 4" x 2 1/8" x 2 1/8" with cover, to be installed in dry location (press box), furnished.	N/A	N/A

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.

#103 Cardinal Red	#73 Maroon	#102 Team Orange	#99 Golden Yellow	#142 Kelly Green	#74 Forest Green	#120 Teal Blue	#72 Electronic Blue	#140 Royal Blue	#121 Midnight Blue	#141 Navy Blue	#104 Medium Purple	#70 Desert Tan	#95 Silver Gray	#76 Print Black
-------------------------	---------------	------------------------	-------------------------	------------------------	------------------------	----------------------	---------------------------	-----------------------	--------------------------	----------------------	--------------------------	----------------------	-----------------------	-----------------------

AGENCY APPROVAL: UL/CUL listed, FCC, CE, INDUSTRY CANADA.

SCOREBOARD: Size 24"L x 8"H x 8"D (7.31 x 2.44 x .20 meters), constructed of aluminum. Scoreboard has 1" white outline striping. Four (4) brackets provided for mounting. Hanging weight approximately 740 lbs. (336 kg).

INTELLIGENT CAPTIONS: (2) 8x48, (4) 8x32, (2) 8x16.

LED UNITS: Seven-bar segmented digits with protective aluminum cover.

POWER (RED/AMBER): 120 VAC, 7.0 Amps, 50/60 Hz. / 240 VAC, 3.5 Amps, 50/60 Hz. Requires earth ground.

POWER (TRANSLUCENT WHITE): 120 VAC, 9.5 Amps, 50/60 Hz. / 240 VAC, 4.7 Amps, 50/60 Hz. Requires earth ground.

BUILT-IN LIGHTNING PROTECTION: All models feature fiber-optic isolation circuitry providing additional protection against lightning strikes.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: NEVCO.COM/WARRANTY-LIMITATION

U.S. SERVICE: 1-800-851-4040

INTERNATIONAL SERVICE: 1-618-664-0360

CANADA SERVICE: 1-800-461-8550



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM