



SOCCER


SCOREBOARDS

MODEL 3617

Size: 24' x 8' x 8" (7.32 x 2.44 x .20 meters)

Approximate hanging weight: 570 lbs. (259 kg) with ETNs: 632 lbs. (287 kg)

Digit Size: 24"/18" Digit Color: High Intensity Red, Amber, or Translucent White



SHOWN WITH OPTIONAL WHITE LEDS



SHOWN WITH OPTIONAL ELECTRONIC TEAM NAMES

Advanced timing features ideal for combination Soccer, Football, Baseball, Softball, Lacrosse and Field Hockey facilities.

- Operate wired or wireless.
- Bright, long lasting, energy efficient LEDs.
- Gasketed digits reduces water intake.
- Includes Possession Indicators, Time Outs Left and built-in Horn.
- Lighted time colon and decimal; automatically adjusts to 1/10th of a second.

* Translucent White LEDs cannot be intermixed with other digit colors on one scoreboard.



MAXIMIZE YOUR IMPACT®

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM

INTEGRATED DISPLAY AND SCORING SOLUTIONS




Model 3617 (Outdoor) Soccer/Lacrosse/Field Hockey Scoreboard

SCOREBOARD/CONTROL OPERATING FEATURES

| MODEL 3617 | MPC(W)-4/5/6 | MPCW-7 | MPCX ₂ WIRELESS |
|---|---|---|---|
| TIMING 24" High Intensity Red, Amber, or Translucent White LED Digits | Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute. | Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute. | Bi-directional UP or DOWN count. Any number can be set between 0:00-99:59. 1/10th seconds display during final minute. |
| TEAM SCORES 24" High Intensity Red, Amber, or Translucent White LED Digits | Displays 0-99 | Displays 0-99 | Displays 0-99 |
| TIME OUTS LEFT 18" High Intensity Red, Amber, or Translucent White LED Digits | Displays 0-9 | Displays 0-9 | Displays 0-9 |
| HALF 24" High Intensity Red, Amber, or Translucent White LED Digits | Displays 0-9 | Displays 0-9 | Displays 0-9 |
| HOME SHOTS 24" High Intensity Red, Amber, or Translucent White LED Digits | Displays 0-99 | Displays 0-99 | Displays 0-99 |
| PENALTY KICK INDICATORS High Intensity Red, Amber, or Translucent White LED | One for each team shaped in the form of a football. | One for each team shaped in the form of a football. | N/A |
| GUEST SHOTS 24" High Intensity Red, Amber, or Translucent White LED Digits | Displays 0-99 | Displays 0-99 | Displays 0-99 |
| TIME OF DAY | In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day". | In place of displaying game time on the scoreboard, the "time out" time may be displayed or the "time of day". | N/A |
| HORN | Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time. | Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time. | Sounds automatically at 0:00 for a minimum of two (2) seconds. May omit automatic horn. Can sound manually at any time. |
| JUNCTION BOX | One (1) 4" x 2 1/8" x 2 1/8" with cover, to be installed in dry location (press box), furnished. | N/A | N/A |
| CONTROL CABLE | One (1) length required of 2-WIRE (coaxial type) 3/4" diameter. Order length required. | N/A | N/A |
| SEGMENT TIMING | Supported. | Supported. | Requires MPCX ₂ segment timer control. |

In addition to the standard 15 colors, Nevco can match any PMS color. Please contact your local Display and Scoring Consultant for pricing information.



AGENCY APPROVAL: UL/CUL listed, FCC, CE, INDUSTRY CANADA.

SCOREBOARD: Size 24'L x 8'H x 8"D (7.32 x 2.44 x .20 meters), constructed of aluminum. Scoreboard has 1" white outline striping. Six (6) brackets provided for mounting. Hanging weight approximately 570 lbs. (259 kg) with ETNs 632 lbs. (287 kg).

CAPTIONS: HOME, GUESTS, SHOTS, SHOTS, HALF, white 15" high. (HOME and GUESTS are omitted when ordered with ETNs.)

LED UNITS: Seven-bar segmented digits with protective aluminum cover.

POWER WITHOUT ETNS (RED/AMBER): 120 VAC, 3.0 Amps, 50/60 Hz. / 240 VAC, 1.5 Amps, 50/60 Hz. Requires earth ground.

POWER WITH ETNS (RED/AMBER): 120 VAC, 4.2 Amps, 50/60 Hz. / 240 VAC, 2.1 Amps, 50/60 Hz. Requires earth ground.

POWER WITHOUT ETNS (TRANSLUCENT WHITE): 120 VAC, 5.1 Amps, 50/60 Hz. / 240 VAC, 2.5 Amps, 50/60 Hz. Requires earth ground.

POWER WITH ETNS (TRANSLUCENT WHITE): 120 VAC, 6.2 Amps, 50/60 Hz. / 240 VAC, 3.1 Amps, 50/60 Hz. Requires earth ground.

BUILT-IN LIGHTNING PROTECTION: All models feature fiber-optic isolation circuitry providing additional protection against lightning strikes.

GUARANTEE: TO VIEW OR RECEIVE THE MOST RECENT COPY OF OUR GUARANTEE, PLEASE VISIT: NEVCO.COM/WARRANTY-LIMITATION

U.S. SERVICE: 1-800-851-4040

INTERNATIONAL SERVICE: 1-618-664-0360

CANADA SERVICE: 1-800-461-8550

BUILD YOUR OWN DISPLAY AND SCORING SYSTEM ONLINE AT:

WWW.NEVCO.COM

U.S. & CANADA: 800-851-4040 INTERNATIONAL: 618-664-0360

FAX: 618-664-0398 E-MAIL: INFO@NEVCO.COM



MAXIMIZE YOUR IMPACT®